

## TECHNICAL CHARACTERISTICS

**SPECIFICATION:** SAEJ30R6

**APPLICATION:** For conveyance of leaded or unleaded fuel

**TUBE:** Black NBR







**REINFORCEMENT:** Polyester Yarn

**COVER:** Black, smooth, NBR / NBR PVC Blended

**TEMPERATURE RANGE:** -20 degrees C to +70 degrees C

**SAFETY FACTOR:** 3:1

**BRANDING:** W=FUEL HOSE SAEJ30R6 SUITABLE FOR UNLEADED NOM INCHES

	I.D	O.D	W.P	W.P	BR	COIL LENGTH
						
Inch	mm	mm	BAR	PSI	mm	mt
3/16"	5	12	20	300	40	10/100
1/4"	6	13	20	300	50	10/100
5/16"	8	15	20	300	65	10/100
3/8"	10	17	20	300	75	10/100
1/2"	13	21	20	300	100	100
7/8"	22	30	20	300	220	50

In response to previous customer enquiries, our suppliers have advised that:

- The Unleaded Fuel Hose is not suitable for submerging
- The Unleaded Fuel Hose does not have a R10 rating
- Using E10 fuel with the Unleaded Fuel Hose will affect the life span of the hose
- The cover of the Unleaded Fuel Hose is resistant to fuel vapour
- The Unleaded Fuel Hose is suitable for use with Diesel fuel
- The Unleaded Fuel Hose is suitable for Ethylene in gas form
- The Unleaded Fuel Hose is compatible with B5 BioFuel