


UF

BLACK UNLEADED FUEL HOSE



TECHNICAL CHARACTERISTICS

- SPECIFICATION:** SAEJ30R6
- APPLICATION:** For conveyance of leaded or unleaded fuel
- TUBE:** Black NBR
- REINFORCEMENT:** Polyester Yarn
- COVER:** Black, smooth, NBR / NBR PVC Blended
- TEMPERATURE RANGE:** -20 degrees C to +70 degrees C
- SAFETY FACTOR:** 3:1
- BRANDING:** W=FUEL HOSE SAEJ30R6 SUITABLE FOR UNLEADED NOM INCHES
Date of manufacture is embossed (YYYY MM)

	I.D	O.D	W.P	W.P	BR	COIL LENGTH
Inch	mm	mm	BAR	PSI	mm	mt
3/16"	5	12	20	300	40	10/100
1/4"	6	13	20	300	50	10/100
5/16"	8	15	20	300	65	10/100
3/8"	10	17	20	300	75	10/100
1/2"	13	21	20	300	100	100
7/8"	22	30	20	300	220	50

In response to previous customer enquiries, our suppliers have advised that:

- Not suitable for submerging
- Does not have a R10 rating
- Using E10 fuel with the hose will affect the life span of the hose
- The cover is resistant to fuel vapour
- Suitable for use with Diesel fuel
- Suitable for Ethylene in gas form
- Compatible with B5 BioFuel