

TECHNICAL CHARACTERISTICS

SPECIFICATION: N/A

APPLICATION: Often used with water pumps and can be used with submersible pumps to move water and other light liquids, horizontal vacuum


TUBE: Strong, smooth plasticised PVC

REINFORCEMENT: Rigid PVC spiral with ACR impact modifiers to improve shock and crush resistance

COVER: Strong, flexible and smooth plasticised PVC

TEMPERATURE RANGE: -5 degrees C to +60 degrees C

SAFETY FACTOR: 3:1

| |  |  |  |  |  |  |
|--------|---|---|---|--|---|---|
| Inch | mm | mm | BAR | PSI | mm | mt |
| 3/4" | 19 | 24 | 8 | 120 | 85 | 30 |
| 1" | 25 | 30 | 8 | 120 | 105 | 10 / 30 |
| 1 1/4" | 32 | 38 | 7 | 105 | 125 | 10 / 30 |
| 1 1/2" | 38 | 44 | 6 | 90 | 150 | 30 |
| 2" | 51 | 58 | 6 | 90 | 205 | 10 / 30 |
| 2 1/2" | 63 | 74 | 4 | 60 | 300 | 30 |
| 3" | 76 | 83 | 4 | 60 | 320 | 30 |